

THROWBOT'2

KNOW BEFORE YOU GO



TB2 PERFORMANCE STATS:

Indoor Range (NLOS): Tested to 150ft/45m Outdoor Range (LOS): Tested to 450ft/137m

Speed: 1.8ft/s; 0.6m/s

Drop Shock Resistance: 30ft/9.1m vertical **Throw Shock Resistance:** 120ft/36m horizontal

Runtime: 110 typical use/160 minutes in

observation mode

Water and Dust Protection: TB2 IP66 & IP67 Compliant OCU3 IP65 & IP67 Compliant

IR Illumination: 25ft/7.62m Audio: One-way, listening only

Image Sensor: Type: Color / Field of View: 60 degrees

Frame Rate: 30 fps

Stated performance parameters are factory-tested and actual performance may vary depending on local environmental conditions.

MECHANICAL SPECS:

Throwbot® 2 Robot

Weight: 1.3 lbs./0.6kg Length: 8.3in/21.1cm Width: 7.9in/20.1cm Height: 4.5in/11.4cm

Operator Control Unit 3 (OCU3)

Height: 6.8in/17.3cm **Width:** 9.7in/24.6cm **Weight:** 2.95lb/1.34kg

Screen Size: 7in/17.75cm Touch Screen

OCU 3 Run Time: 160 Minutes